

SAFETY DATA SHEET



SECTION 1

PRODUCT IDENTIFICATION

Product Name:	Aquasheen Transparent Primer Sealer - Part A
Recommended Use:	2 pack epoxy pool paint primer sealer (when Part A mixed with Part B)
Supplier Information:	Aquasheen Unit 1/34 Truganina Rd Malaga 6090 Phone: 1300 437 699 www.epoxypoolpaint.com.au Emergency Phone: 1300 437 699

SECTION 2

HAZARD IDENTIFICATION

Hazard Classification:	<ul style="list-style-type: none"> • DANGEROUS GOODS according to the criteria of the ADG code • HAZARDOUS CHEMICAL according to the criteria of Safe Work Australia • Flammable Liquids, Category 3 • Skin corrosion / Irritation, Category 2 • Serious eye damage/irritation, Category 2 • Skin sensitiser, Category 1 • Specific Target Organ Toxicity (single exposure), Category 3 • Label elements: • Pictograms <div style="display: flex; justify-content: space-around; align-items: center;"> <div style="text-align: center;">  <p>FLAMMABLE</p> </div> <div style="text-align: center;">  <p>IRRITANT</p> </div> </div> <ul style="list-style-type: none"> • Signal Word: WARNING
------------------------	---

<p>Hazard Statements:</p>	<p>H226 Flammable liquid and vapour</p> <p>H315 Causes skin irritation</p> <p>H319 Causes serious eye irritation</p> <p>H317 May cause an allergic skin reaction</p> <p>H335 May cause respiratory irritation</p>
<p>Precautionary Statements:</p>	<p>GENERAL</p> <p>P101 If medical advice is needed, have product container or label at hand</p> <p>P102 Keep out of the reach of children</p> <p>P103 Read label before use</p> <p>PREVENTATIVE</p> <p>P210 Keep away from heat/sparks/open flames/hot surfaces – No Smoking</p> <p>P233 Keep container tightly closed</p> <p>P240 Ground/bond container and receiving equipment</p> <p>P241 Use explosion proof electrical/ventilation/lighting equipment</p> <p>P242 Use only non-sparking tools</p> <p>P243 Take precautionary measures against static discharge</p> <p>P261 Avoid breathing mists/vapours/spray</p> <p>P264 Wash thoroughly after handling</p> <p>P271 Use only outdoors or in a well-ventilated area</p> <p>P272 Contaminated work clothing should not be allowed out of the workplace</p> <p>P280 Wear protective gloves/eye protection/face protection</p>

RESPONSE

P302 IF ON SKIN: Wash with plenty of soap and water
+

P352

P303 IF ON SKIN (or hair):Take off contaminated
+

P361

P353 Rinse skin with water/shower

P304 IF INHALED: Remove the victim to fresh air and
+

P340 keep at rest in a position comfortable for
breathing

P305 IF IN EYES: Rinse cautiously with water for several
+

P351 minutes.

P338 Remove contact lenses, if present and easy to do.
Continue rinsing

P308 IF exposed or concerned: Get medical
+ P313 advice/attention

P312 Call a POISON CENTER or doctor/physician if you
feel unwell

P314 Get medical advice/attention if you feel unwell

P333 + If skin irritation or rash occurs: Get medical
P313 advice/attention

P337 + If eye irritation persists: get medical
P313 advice/attention

P362 Take off contaminated clothing and wash before
reuse

P370 In case of fire: Use foam/water spray/fog for
+

P378 extinction

P391 Collect spillage

STORAGE

P403 Store in a well-ventilated place. Keep container
+

P233 tightly closed

	P403	Store in a well-ventilated place. Keep cool
	+	
	P235	
	P405	Store locked up
	DISPOSAL	
	P501	Dispose of contents/container in accordance with local regulations

SECTION 3		
COMPOSITION		
Bisphenol A / bisphenol A diglycidyl ether polymer	25036-25-3	20-30%
Xylene	1330-20-7	20-30%
Propylene Glycol Monomethyl Ether Acetate	108-65-6	10-20%
2-Butoxyethanol	111-76-2	<10%
Methyl ethyl ketone	78-93-3	<10%
n-Butyl Acetate	123-86-4	<10%
Other Non-Hazardous Materials to 100%		

Note – product contains <0.1% benzene

Proportion is % weight per weight

All the constituents of this material are listed on the Australian Inventory of Chemical Substances (AICS)

SECTION 4
FIRST AID MEASURES
Poisons Information Centres in each State capital city can provide additional assistance for scheduled poisons.
DESCRIPTION OF NECESSARY FIRST AID MEASURES
INHALATION: Keep victim calm and remove to fresh air if safe to do so. If rapid recovery does not occur, transport to nearest medical facility for additional treatment.
SKIN CONTACT: If skin contact occurs, remove contaminated clothing and wash skin thoroughly with water and follow by washing with soap if available. Transport to nearest medical facility for additional treatment if necessary.
EYE CONTACT: If in eyes, hold eyes open, flood with water for at least 15 minutes. Seek immediate medical assistance.

INGESTION: If swallowed, do NOT induce vomiting. Transport to nearest medical facility for additional treatment. If vomiting occurs spontaneously, keep head below hips to prevent aspiration.

SYMPTOMS CAUSED BY EXPOSURE

INHALATION: Breathing of high vapour concentrations may cause central nervous system depression resulting in dizziness, light-headedness, headache, nausea and loss of coordination. Continuous inhalation may result in unconsciousness and death.

SKIN: May include burning sensation and/or a dried/cracked appearance.

EYE: May include burning sensation, redness, swelling and/or blurred vision.

INGESTION: May include coughing, choking, wheezing, difficulty in breathing, chest congestion, shortness of breath and/or fever.

SECTION 5

FIRE FIGHTING MEASURES

SUITABLE EXTINGUISHING MEDIA:

Foam, water spray or fog, carbon dioxide, dry chemical powder. Do not use water in a jet.

SPECIFIC HAZARDS:

Carbon monoxide may be evolved if incomplete combustion occurs. Will float and can be reignited on surface water. Vapour is heavier than air, can spread along the ground and distant ignition is possible.

FIRE FIGHTING ADVICE:

Class 3 Flammable liquid. On burning this product may emit toxic fumes. Heating can cause expansion or decomposition leading to violent rupture of containers. Keep containers cool with water spray. Firefighters to wear self-contained breathing apparatus if risk of exposure to vapour or decomposition products.

SECTION 6

ACCIDENTAL RELEASE MEASURES

PERSONAL PRECAUTIONS, PROTECTIVE EQUIPMENT AND EMERGENCY PROCEDURES

Avoid contact with spilled or released material. Shut off leaks, if possible without personal risks. Isolate hazard area and deny entry to unnecessary or unprotected personnel. Remove all sources of ignition in the surrounding area. Take

precautionary measures against static discharge. Ensure electrical continuity by bonding and earthing all equipment.

ENVIRONMENTAL PRECAUTIONS

Use appropriate containment to avoid environmental contamination. Prevent from spreading and entering waterways using sand, earth or other appropriate barriers. Attempt to disperse the vapour or to direct its flow to a safe location for example by using fog sprays. Ventilate contaminated area thoroughly.

METHODS AND MATERIALS FOR CONTAINMENT AND CLEANING UP

For small spills (< 1 drum), transfer by mechanical means to a labelled, sealable container for product recovery or safe disposal. Allow any residues to evaporate or use an appropriate absorbent material and dispose of safely.

For larger spills (> 1 drum), transfer by means such as a vacuum truck to a salvage tank for recovery or disposal. Do not flush residues with water. Retain as contaminated waste. Allow any residues to evaporate or use an appropriate absorbent material and dispose of safely.

SECTION 7

HANDLING AND STORAGE

PRECAUTIONS FOR SAFE HANDLING

Flammable product. Avoid breathing vapours. Handle and open containers with care in a well ventilated area. Ensure that the workplace is ventilated such that the Occupational Exposure limit is not exceeded. Avoid contact with skin, eyes and clothing. Wash thoroughly after handling. Do not eat, drink or smoke in contaminated areas. Electrostatic charges may be generated during transfer. Electrostatic discharge may cause fire. Ensure electrical continuity by earthing all equipment. Flameproof equipment necessary in area where chemical is being used. Vapours may accumulate in low or confined areas.

CONDITIONS FOR SAFE STORAGE, INCLUDING ANY INCOMPATIBILITIES

Bulk storage tanks should be banded. Store in a well-ventilated area, away from sunlight, ignition sources and other sources of heat. Do not store near strong oxidants.

SECTION 8

EXPOSURE CONTROLS AND PERSONAL PROTECTION

NATIONAL EXPOSURE LIMITS

No value has been assigned for this specific product by the National Occupational Health and Safety Commission (NOHSC) Worksafe Australia

However, exposure standards for constituents:

Material	TWA		STEL		Notices
	ppm	mg/m ³	ppm	mg/m ³	
Xylene	80	350	150	655	SK
Methyl Isobutyl ketone	50	205	75	307	-
n-Butyl Alcohol	50	152	-	-	-

TWA:

The Time Weighted Average airborne concentrations over an eight-hour working day, for a five day working week over an entire working life.

STEL:

(Short Term Exposure Limit) The average airborne concentration over a fifteen minute period which should not be exceeded at any time during a normal eight-hour work day.

SK NOTICE:

Absorption through the skin may be a significant source of exposure. The exposure standard is invalidated if such contact should occur.

According to current knowledge, these concentrations should neither impair the health of, nor cause undue discomfort to, nearly all workers.

These exposure standards are guides to be used in the control of Occupational Health Hazards. All atmospheric contamination should be kept as low as is practicable.

Exposure standards should **NOT** be used as the defining line between safe and dangerous concentrations of chemicals. They are **NOT** a measure of relative toxicity.

BIOLOGICAL MONITORING

No biological limit allocated.

ENGINEERING CONTROLS

Ensure that adequate ventilation is provided. Maintain air concentrations below recommended exposure standards. Avoid generating and inhaling mists and vapours. Keep containers closed when not in use. **DO NOT** enter confined spaces where vapour may have collected.

INDIVIDUAL PROTECTION MEASURES

EYE AND FACE PROTECTION:

Wear safety goggles.

SKIN PROTECTION:

Use solvent resistant gloves, nitrile for longer term protection or PVC and neoprene for incidental splashes.

RESPIRATORY PROTECTION:

If work practices do not maintain airborne levels below the exposure standard, use appropriate respiratory protection equipment. When using respirators, select an appropriate combination of mask and filter. Select a filter for organic gases and vapours (boiling point > 65°C). Respirators should comply with AS1716 or an equivalent approved by a state/territory authority.

THERMAL HAZARDS:

Not applicable

SECTION 9

PHYSICAL PROPERTIES

APPEARANCE:

Viscous liquid

SOLUBILITY:

Insoluble in water

Odour:	Solvent	Density @ 20°C:	~0.96 kg/lit
pH:	NAP	Flash point & Method:	~ 24°C Closed Cup
Vapour Pressure 20°C (mm Hg):	~ 5.0 kPa	Upper Explosive Limit (UEL):	8.0%
Vapour Density (Air = 1)	~3.5	Lower Explosive Limit (LEL):	1.2%
Initial Boiling Point & Range °C:	~ 110-145	Ignition Temperature °C:	NAV
Freezing Point °C:	NAV	Percent Volatiles (by weight):	~ 71%

NAP = Not Applicable, NAV = Not Available

SECTION 10

STABILITY AND REACTIVITY

REACTIVITY

Stable under normal conditions of use.

CHEMICAL STABILITY

Stable under normal conditions of use.

POSSIBILITY OF HAZARDOUS REACTIONS

Stable under normal conditions of use.

CONDITIONS TO AVOID

Avoid heat, sparks, open flames and other ignition sources.

INCOMPATIBLE MATERIALS

Strong oxidising agents.

HAZARDOUS DECOMPOSITION PRODUCTS

Thermal decomposition is highly dependent on conditions. A complex mixture of airborne solids, liquids, gases, including carbon monoxide, carbon dioxide and other organic compounds will be evolved when this material undergoes combustion or thermal or oxidative degradation.

SECTION 11	
TOXICOLOGICAL INFORMATION	
Acute toxicity:	Expected to be of low toxicity - LD50 Oral (rat) > 2000 mg/kg LC50 Inhalation (rat, 4h) > 20 mg/l LD50 Dermal (rabbit) > 2000 mg/kg
Skin corrosion/irritation:	May cause moderate skin irritation. Prolonged contact may cause defatting of skin which can lead to dermatitis.
Serious eye damage/irritation:	Irritating to eyes.
Respiratory or skin sensitisation:	May cause skin sensitisation.
Germ cell mutagenicity:	Not expected to be mutagenic
Carcinogenicity:	Not expected to be carcinogenic.
Reproductive toxicity:	Not expected to impair fertility
Specific Target Organ Toxicity (STOT) – single exposure:	Inhalation of vapours or mists may cause irritation to the respiratory system.
Specific Target Organ Toxicity (STOT) – repeated exposure:	Central nervous system: repeated exposure affects the nervous system. Effects seen at high doses only. Respiratory system: repeated exposure affects the respiratory system. Effects seen at high doses only.
Aspiration hazard:	Not expected to be an aspiration hazard.

SECTION 12

ECOLOGICAL INFORMATION

ECOTOXICITY

For constituent Xylene:

Acute Toxicity:	Fish	Toxic, $1 < LC/EC/IC\ 50 \leq 10\text{mg/l}$.
Acute Toxicity:	Invertebrates	Toxic, $1 < LC/EC/IC\ 50 \leq 10\text{mg/l}$.
Acute Toxicity:	Algae	Toxic, $1 < LC/EC/IC\ 50 \leq 10\text{mg/l}$.
Acute Toxicity:	Microorganisms	Data not available
Chronic toxicity:	-	Data not available

PERSISTENCE AND DEGRADABILITY

Readily biodegradable. Oxidises by photo-chemical reactions in air.

BIOACCUMULATIVE POTENTIAL

Not expected to bioaccumulate significantly.

MOBILITY IN SOIL

Floats on water, highly mobile and may contaminate groundwater.

OTHER ADVERSE EFFECTS

Data not available.

SECTION 13

DISPOSAL CONSIDERATIONS

- Do not pour unwanted product down the drain.
- Keep unwanted product in sealed containers for disposal via special chemical waste collections.
- Empty paint containers should be left open in a well ventilated area to dry out. When dry, recycle steel containers via steel can recycling programs.
- Disposal of empty paint containers via domestic recycling programs may differ between local authorities.
- Check with your local council first.

SECTION 14

TRANSPORT INFORMATION

Classified as Dangerous Goods by the criteria of the Australian Dangerous Goods Code (ADG7 Code) for transport by road or rail.

UN Number:	1263	HAZCHEM:	.3Y
UN Proper Shipping Name:	PAINT	Packaging Group:	III
Class and Sub Risk:	3 Flammable Liquid		

Special Precautions: Not to be loaded with explosives (Class 1), flammable gases (Class 2.1) in bulk, poisonous gases (Class 2.3), spontaneously combustible substances (Class 4.2), oxidising agents (Class 5.1), organic peroxides (Class 5.2) and radioactive substances (Class 7), however, exemptions may apply.

SECTION 15

REGULATORY INFORMATION

- Hazardous according to Safe Work Australia
- Poisons Schedule (Australia): S5

SECTION 16

OTHER INFORMATION

DATE OF PREPARATION:

September 2019

Version 1.01

GENERAL:

The information contained herein is based on data considered accurate and reliable to the best of our knowledge and belief as of the date compiled. However no warranty is expressed or implied regarding the accuracy of the data or the results to be obtained from the use thereof. Aquasheen assumes no responsibility for personal injury or property damage to vendors, users or third parties caused by the material. Such users or vendors assume all risks associated with the use of the material. It is the user's responsibility to satisfy themselves as to the suitability and completeness of the information for their own particular use. The users must determine whether the use of the information and data is in accordance with the local laws and regulations.